



HOTMELT TAPE

FEATURES:

- **EXCELLENT PROCESSING** PERFORMANCE WITH SUPERIOR ADHESION PROPERTIES, HOLDING FORCE AND TACTILE STRENGTH
- RELIABLY SEALS A VARIETY OF **BOX TYPES**
- DOES NOT LEAVES BEHIND **RESIDUE ON ROLLERS**





		1		
THICKNESS	ITEM ID	COLOR	DESCRIPTION	SELLING UNIT
1.6 MIL	16HMT255T	TAN	48mm x 50m	36 rls/cs, 100 cs/plt
	16HMT2110T		48mm x 100m	36 rls/cs, 75 cs/plt
	16HMT21000T		48mm x 914m	6 rls/cs, 64 cs/plt
	16HMT21000C	CLEAR	48mm x 914m	
	16HMT31000C		72mm x 914m	4 rls/cs, 64 cs/plt
	16HMT2110C		48mm x 100m	36 rls/cs, 75 cs/plt
	16HMT3110C		72mm x 100m	24 rls/cs, 75 cs/plt
1.8 MIL	HMT2110C	CLEAR	48mm x 100m	36 rls/cs, 75 cs/plt
	НМТ3110С		72mm x 100m	24 rls/cs, 75 cs/plt
	HMT21000C		48mm x 914m	6 rls/cs, 64 cs/plt
	НМТ31000С		72mm x 914m	4 rls/cs, 64 cs/plt
1.85 MIL	19HMT2110C	CLEAR	48mm x 100m	36 rls/cs, 75 cs/plt
	19HMT3110C		72mm x 100m	24 rls/cs, 75 cs/plt
	19HMT21000C		48mm x 914m	6 rls/cs, 64 cs/plt
	19HMT31000C		72mm x 914m	4 rls/cs, 64 cs/plt
	19HMT21500C		48mm x 1371m	6 rls/cs, 36 cs/plt
1.95 MIL	20HMT2110C	CLEAR	48mm x 100m, Cold Temperature	36 rls/cs, 75 cs/plt
	20HMT3110C		72mm x 100m, Cold Temperature	24 rls/cs, 75 cs/plt
	20HMT21000C		48mm x 914m, Cold Temperature	6 rls/cs, 64 cs/plt
	20HMT31000C		72mm x 914m, Cold Temperature	4 rls/cs, 64 cs/plt
2.05 MIL	20HMT2110C-RC	CLEAR	48mm x 100m, For recycled boxes	36 rls/cs, 75 cs/plt
	20HMT3110C-RC		72mm x 100m, For recycled boxes	24 rls/cs, 75 cs/plt
2.44 MIL	25HMT2110C	CLEAR	48mm x 100m	36 rls/cs, 52 cs/plt
	25HMT3110C		72mm x 100m	24 rls/cs, 52 cs/plt
	25HMT2110T	TAN	48mm x 100m	36 rls/cs, 52 cs/plt
	25HMT3110T		72mm x 100m	24 rls/cs, 52 cs/plt
2.83 MIL	30HMT255C	CLEAR	48mm x 50m	36 rls/cs, 75 cs/plt
	30HMT355C		72mm x 50m	24 rls/cs, 75 cs/plt
3.46 MIL	35HMT255C	CLEAR	48mm x 50m	36 rls/cs, 75 cs/plt
	35HMT355C		72mm x 50m	24 rls/cs, 75 cs/plt

YOUR SOURCE FOR INDUSTRIAL PACKAGING, JAN/SAN AND SAFETY SUPPLIES





















