



Certified to  
ISO 9001:2015



## Product Data Sheet

### 1.6 Mil Carton Sealing Tape



#### Product Description:

General performance, economical carton sealing tape with acrylic emulsion adhesive with performance in all temperatures. Resistant to weathering and yellowing.

**Backing:**

0.9 Mil

**Adhesive:**

Acrylic emulsion adhesive.

**Color(s):**

Clear.

**Elongation  
(% At Break)**

153% (ASTM D3759)

**Tensile Strength**

17.13 lbs. / in (ASTM D3759)

**Adhesion to Steel**

27.59 ozf / in (ASTM D3330)

**Total Thickness:**

1.6 Mil (ASTM D3652)

**Temperature  
Range:**

23°F to 104°F (Application)  
0°F to 200°F (Operating)

**Packaging**

N/A

**Country of Origin**

N/A

#### Item ID Numbers

**Here:** 16CST2110C &  
16CST3110C

#### Wrap-Tite, Inc.

6200 Cochran Rd.  
Solon, Ohio 44139

**Toll Free:** 888-WRAP-TITE

**Fax:** 440-349-5432

www.wraptite.com -  
info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.