



## Product Data Sheet

### 1.6 Mil Hotmelt SELECT Tape

#### Product Description:

HMT Select Tape is designed for closing high recycled content corrugated boxes. It gives a fool proof closure in both hand and machine application. The Synthetic Rubber Glue provides exceptionally quick tack and strong adhesion making the boxes safe and secure. The superior shear strength makes sure the boxes are closed for the longest time. The extremely easy unwind makes it a pleasure to use this tape.



#### Item ID Numbers Here:

16HMTS2110T, 16HMTS2110C,  
16HMTS3110C,  
16HMTS21000C,  
16HMTS21000T,  
16HMTS31000C

**Wrap-Tite, Inc.**  
6200 Cochran Rd.  
Solon, Ohio 44139  
**Toll Free:** 888-WRAP-TITE  
**Fax:** 440-349-5432  
www.wraptite.com -  
info@wraptite.com

<b>Backing:</b>	Biaxially oriented polypropylene cast film
<b>Adhesive:</b>	Synthetic Rubber
<b>Color:</b>	Clear (C) / Tan (T)
<b>Elongation (% At Break)</b>	150%
<b>Tensile Strength</b>	20lbs/in
<b>Adhesion to Steel</b>	36 Oz/in.
<b>Total Thickness:</b>	1.6 Mil
<b>Film Thickness (Micron)</b>	25 Micron
<b>Temperature Range:</b>	+45°F to +120°F (Application) -10°F to +140°F (Operating)
<b>Country of Origin</b>	PRC

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.