



6200 Cochran Rd.
 Solon, Ohio 44139
 888-972-7848 - Toll Free
 440-349-5432 - Fax
 www.wraptite.com -
 info@wraptite.com



Product Data Sheet

2.5 Mil Carton Sealing Tape



Product Description:

High-performance grade acrylic packaging tape for heavy duty manual and automated industrial sealing of cartons exposed to rough handling and load stress. With excellent quick stick and superior clarity in a wide range of applications, environments, and temperatures

Backing:	1.6 Mil
Adhesive:	Acrylic emulsion adhesive.
Color(s):	Clear.
Elongation (% At Break)	166% (ASTM D3759)
Tensile Strength	22 lbs. / in (ASTM D3759)
Adhesion to Steel	34.7 ozf / in (ASTM D3330)
Total Thickness:	2.5 Mil (ASTM D3652)
Temperature Range:	23°F to 104°F (Application) 0°F to 200°F (Operating)
Adhesive Thickness:	0.9 Mil
Shear Strength (on paper):	3.33 hr. (min.) (ATSM D3654)

Item ID Numbers

Here: 25CST2110C &
25CST3110C

Wrap-Tite, Inc.

6200 Cochran Rd.
Solon, Ohio 44139

Toll Free: 888-WRAP-TITE

Fax: 440-349-5432
www.wraptite.com -
info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.