



Product Data Sheet

2.0 mil HMT Select Tape



Effective 12/2021

Product Description:

HMT Select Tape is **designed for closing high recycled content corrugated boxes**. It gives a fool proof closure in both hand and machine application. The Synthetic Rubber Glue provides **exceptionally quick tack and strong adhesion** making the boxes safe and secure. The **superior shear strength** makes sure the boxes are closed for the longest time. The **extremely easy unwind** makes it a pleasure to use this tape.

Item ID Numbers:

**20HMTS2110C, 20HMTS21000C,
20HMTS3110C, 20HMTS31000C**

Nominal Values:



Backing:	Biaxially oriented polypropylene cast film	
Film thickness:	30 Micron	
Adhesive:	Synthetic Rubber	
Color:	Clear	
Total Thickness:	2.0 MIL	
Adhesion to Steel: (Min.)	28 oz/in	(ASTM D3330)
Tensile Strength: (Min.)	25 lb./in	(ASTM D3759)
Elongation: (Max)	178%	(ASTM D3759)
Temperature Range:	+45°F to +120°F (Application) -10°F to +140°F (Operating)	

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

