



Product Data Sheet

20HMT Series Hotmelt Tape (Cold Temp.Tape)



Effective 02/2018

Product Description:

It is an industrial strength Cold Temperature packaging tape that has been formulated to be used in applications at refrigerated temperatures or at room temperature and then stored in low temperature environments which include produce packaging, dairy facilities, meat and poultry processing plants. This product has a conformable film backing and has been combined with a consistent pressure sensitive hot melt high quality adhesive coating

Item ID Numbers:

20HMT2110C, 20HMT3110C

Nominal Values:

Backing:	1.3 MIL BOPP film
Adhesive:	Synthetic Rubber /Resin
Color:	Clear
Total Thickness:	1.95 MIL (ASTM D3652)
Adhesion to Steel:	26 oz/in (ASTM D3330)
Tensile Strength:	22 lb/in (ASTM D3759)
Elongation (% at break)	120% (ASTM D3759)
Temperature Range:	+35°F to +120°F (Application) -40°F to 140°F (Operating)
Government Compliance:	Complies with the Federal Food, Drug and Cosmetic Act, CFR Title 21, Subpart B, Par. 175.105 (covers the use of pressure-sensitive adhesives and tapes for 'indirect contact' food packaging, such as box sealing). CID A-A-1684C.

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.

6200 Cochran Rd.
Solon, Ohio 44139

Toll Free: 888-WRAP TITE (972-7848)

Fax: 440-349-5432

www.wraptite.com - info@wraptite.com

