



PVC Tape



Product Data Sheet

Effective 04/2019

Product Description:

This pressure sensitive tape provides instant adhesion, possesses excellent quick stick properties and sticks to a wide variety of irregularly shaped surfaces. The natural rubber and resin adhesive have been specifically formulated to provide good instant adhesion to fiberboard, plastic, glass, metallic, printed and painted surfaces. Typical applications would include; carton closure in cold temperature environments, recycled cartons, color coding, strapping, bundling, unitizing, packaging, palletizing, etc.

Item ID Numbers:

23PVC255R

Nominal Values:

Thickness:	2.3 mils
Adhesive:	Natural Rubber and Resins
Adhesive to steel:	18 oz./in width (ASTM D3330)
Color:	Red
Backing:	PVC Film
Backing Thickness:	1.5 mils
Tensile Strength:	28 lb./ in (ASTM D3759)
Elongation at break:	80 % (ASTM D3759)
Service Temperature:	20 ⁰ F -140 ⁰ F
Recommended Storage Condition	Store in original packaging in a cool, clean dry place away from direct sunlight. Temperature of 40 -80 ⁰ F (4-26 ⁰ C) and relative humidity of 40 to 50% relative humidity is recommended. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES MORE THAN THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax : 440-349-5432
www.wraptite.com - info@wraptite.com

