



30 HMT Series Hotmelt Tape



Product Data Sheet

Effective 02/2018

Product Description:

Biaxially-oriented polypropylene (BOPP) film carton sealing tape manufactured with pressure sensitive hot melt adhesive. Excellent processing performance with superior adhesion properties, holding force, tensile strength and reliable seals to a variety of boxes.

Item ID Numbers:

30 HMT255C, 30HMT355C

Nominal Values:

Backing:	1.97 MIL BOPP film
Adhesive:	Hotmelt adhesive coating.
Colors:	Clear
Total Thickness:	2.83 MIL (ASTM D3652)
Adhesion to Steel:	56 oz/in (ASTM D3330)
Tensile Strength:	45 lb/in (ASTM D3759)
Elongation (% at break)	200% (ASTM D3759)
Temperature Range:	50°F to 110°F (Application) 30°F to 140°F (Operating)
Government Compliance:	Meets CID A-A-1684C, Complies with environmental considerations of ASTM D 1974-92, ROHS complaint

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
 6200 Cochran Rd.
 Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

