



Product Data Sheet

Shield *SELECT* Duct Tape



Product Description:

Our Shield Select brand of Duct tape can be used for maintenance and general repair, joint sealing, pipe wrapping, bundling, patching, mending and heavy-duty box sealing.

Backing:	PE Film
Adhesive:	Synthetic Rubber
Color(s):	Silver & Black
Reinforcement:	PET Cloth
Elongation (% At Break)	10% (ASTM D3759)
Tensile Strength	11 lbs. / in (ASTM D3759)
Adhesion to Steel	36 ozf / in (ASTM D3330)
Total Thickness:	6 Mil (ASTM D3652)
Temperature Resistance:	+32°F to +160°F
Country of Origin:	N/A

Item ID Numbers

Here: DTS6048, DTS6072, DTS6048B

Wrap-Tite, Inc.
 6200 Cochran Rd.
 Solon, Ohio 44139
Toll Free: 888-WRAP-TITE
Fax: 440-349-5432
www.wraptite.com -
info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.