







Product Data Sheet

Shield SELECT Duct Tape

	Product Descripton: Our Shield Select brand of Duct tape can be used for maintenance and general repair, joint sealing, pipe wrapping, bundling, patching, mending and heavy-duty box sealing.	
	Backing:	PE Film
	Adhesive:	Synthetic Rubber
	Color(s):	Silver & Black
	Reinforcement:	PET Cloth
	Elongation (% At Break)	10% (ASTM D3759)
	Tensile Strength	14 lbs. / in (ASTM D3759)
Wrap-Tite, Inc. 6200 Cochran Rd. Solon, Ohio 44139 Toll Free: 888-WRAP-TITE Fax: 440-349-5432 www.wraptite.com - info@wraptite.com	Adhesion to Steel	43 ozf / in (ASTM D3330)
	Total Thickness:	7 Mil (ASTM D3652)
	Temperature Resistance:	+32°F to +160°F
	Country of Origin:	N/A

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.