



Product Data Sheet

Color Carton Sealing Tape



Effective 01/2016

Product Description:

General Performance, economical carton sealing tape with acrylic emulsion adhesive with good all temperature performance and resistance to weathering and yellowing.

Item ID Numbers:

234805-R, 234805-L, 234805-G, 234805-W, 234805-Y, 234805-O, 234805-B, 234810-R, 234810-L, 234810-G, 234810-W, 234810-Y, 234810-O, 234810-B, 237205-R, 237205-L, 237205-G, 237205-W, 237205-Y, 237205-O, 237205-B, 2348914-B, 2348914-R, 2348914-L, 2348914-Y, 2348914-G, 2348914-W

Nominal Values:

Backing:	1.2 MIL BOPP film
Colors:	Red, Blue, Green, White, Yellow, Orange & Black
Total Thickness:	2.0 MIL
Adhesion to Steel:	22.8 oz/in (ASTM D3330)
Adhesion to Corrugated:	22.8 oz/in (ASTM D3330)
Tensile Strength:	19.7 lb/in (ASTM D3759)
Elongation:	179% (ASTM D3759)
Temperature Range:	32°F to 150°F (Application) -30°F to 200°F (Operating)

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Wrap Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP TITE (972-7848)
Fax: 440-349-5432
www.wraptite.com - info@wraptite.com

