

**Product Description:**

A high tensile strength, high adhesion, rubber based, uni-directional, glass reinforced pressure sensitive tape designed for many demanding packaging applications.

**Item ID Numbers:**

FTI3912, FTI3918, FTI3924, FTI3948

**Nominal Values:**

Backing:	Biaxially-Oriented Glass Reinforced Polypropylene Film
Adhesive:	Synthetic Rubber Resin
Colors:	White
Total Thickness:	4.8 MIL
Peel Adhesion:	110 oz./in
Tensile Strength:	148 lb./in
Elongation:	5%

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NOWARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**Wrap Tite, Inc.**  
6200 Cochran Rd.  
Solon, Ohio 44139  
**Toll Free:** 888-WRAP TITE (972-7848)  
**Fax:** 440-349-5432  
[www.wraptite.com](http://www.wraptite.com) - [info@wraptite.com](mailto:info@wraptite.com)

