



## Product Data Sheet

# WOLVERINE Water Activated Gum Tape

### Product Description:

Wolverine 5.0 Heavy Water-activated reinforced kraft paper tape is mainly used to replace pressure sensitive adhesive tape usually used for carton sealing. Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on light weight to average cartons up to 49 pounds (22 kg).



	<b>Backing:</b>	TOP	25 lb 40 g/m <sup>2</sup> Kraft Paper
		BOTTOM	25 lb 40 g/m <sup>2</sup> Kraft Paper
	<b>Reinforcement</b>	MD	70mm 75 (2-1-1-1-2) Fiberglass
		CD	28mm 150 (1-1-1) Fiberglass Diamond Pattern
<b>Item ID Numbers Here:</b>	<b>Tensile Strength:</b>	MD	79 lbs/in (ASTM D-3759)
GTHS70KAR-WT		CD	21 lbs/in (ASTM D-3759)
<b>Storage information:</b> It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 39°F to 78° F and the humidity shall be between 40% and 50%. Rotate inventory recommended.	<b>Composite Adhesive:</b>		Polymeric Copolymer
	<b>Water-Activated Adhesive:</b>		Starch Adhesive
	<b>Color:</b>		Kraft
<b>Total Thickness:</b>		6.3 mil	
<b>Country of Origin</b>		PRC	
<b>Wrap-Tite, Inc.</b> 6200 Cochran Rd. Solon, Ohio 44139 <b>Toll Free:</b> 888-WRAP-TITE <b>Fax:</b> 440-349-5432 <a href="http://www.wraptite.com">www.wraptite.com</a> - <a href="mailto:info@wraptite.com">info@wraptite.com</a>			

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.