

# WRAP TITE

## Product Data Sheet

**WAT Kraft Gum Tape  
Industrial Grade**



Effective 01/2017

### Product Description:

3-Way fiberglass reinforced natural Kraft carton sealing tape, manufactured with water activated adhesive. Recommended for use on light weight to average cartons up to 30 pounds.

### Item ID Numbers:

GTI72KAR-IT

### Nominal Values:

|   |   |
|---|---|
| Top Ply:  | 23 lb (37 g/m <sup>2</sup> ) Natural Kraft Paper (virgin fibers)  |
| Bottom Ply:   | 23 lb (37 g/m <sup>2</sup> ) Natural Kraft Paper (virgin fibers)  |
| Laminating Adhesive:  | High Melt Index Polypropylene Based Co-Polymer                    |
| Water-Activated Adhesive:   | Chemically Grafted Starch Copolymer Adhesive, Designated as S3911 |
| MD Reinforcement:   | (1-1-1-1) 75 Fiberglass (per 72mm), ½" spacing                    |
| CD Reinforcement:   | (1-1-1) 150 Fiberglass, 1.10" spacing, 44 degree angle            |
| Total Basis Weight:   | 79.2 lb   |
| Physical Properties:  |   |
| Caliper:  | 6.3 mils ( 0.16 mm )  |
| MD Tensile:   | 74 lbs/in ( 324 N/25 mm )   |
| CD Tensile:   | 26 lbs/in ( 114 N/25 mm )   |
| Adhesion(Water at recommended 110 <sup>0</sup> F/ 43 <sup>0</sup> C): |   |
| Fipago:   |   |
| 2/0   | 49  |
| 2/1   | 71  |
| 5/0   | 75  |
| 15/0  | 90  |
| McLaurin:   | 86  |

(Tolerance +/- 10%); We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**Wrap Tite, Inc.**  
6200 Cochran Rd.  
Solon, Ohio 44139  
**Toll Free: 888-WRAP TITE (972-7848)**  
**Fax: 440-349-5432**  
[www.wraptite.com](http://www.wraptite.com) - [info@wraptite.com](mailto:info@wraptite.com)

