



Product Data Sheet

WOLVERINE Water Activated Gum Tape

Product Description:

Wolverine 500.0 Industrial Water-activated Non-reinforced kraft paper tape is mainly used to replace pressure sensitive adhesive tape usually used for carton sealing. Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads.



Storage information:

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 39°F to 78° F and the humidity shall be between 40% and 50%. Rotate inventory recommended.

Item ID Numbers Here:

GTIS70KAR-WT

Wrap-Tite, Inc.

6200 Cochran Rd.
Solon, Ohio 44139

Toll Free: 888-WRAP-TITE

Fax: 440-349-5432
www.wraptite.com -

Email: info@wraptite.com

Backing:		100 g/m ² Kraft Paper
Tensile Strength:	MD	49 lbs/in (ASTM D-3759)
	CD	17 lbs/in (ASTM D-3759)
Composite Adhesive:		Polymeric Copolymer
Water-Activated Adhesive:		Starch Adhesive
Color:		Kraft
Total Thickness:		6.7 mil
Country of Origin		PRC

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.