



## Product Data Sheet

### Shield Tape *SELECT* - Economy Masking Tape

#### Product Description:

Economy Grade Masking Tape for general use and simple jobs in the building, construction and industrial sectors. Recommended to remove within 30 hours.

- Good addition even on uneven surfaces - Well conformable to most shaped surfaces
- Hand Tearable - Easy removal, if removed as soon as paint is dry, without leaving residue



<b>Backing:</b>	Crepe Paper
<b>Adhesive:</b>	Natural Rubber
<b>Color:</b>	White
<b>Elongation (% At Break)</b>	6 % (PSTC 131)
<b>Tensile Strength</b>	13.48 lb./ in (PSTC 131)
<b>Adhesion to Steel</b>	21.59 oz./in width (PSTC 101 )
<b>Total Thickness:</b>	5.11 Mil
<b>Initial Tack</b>	6#
<b>Temperature Range:</b>	41° F ~ 140° F
<b>Holding Power</b>	10H

#### Item ID Numbers

**Here:** NRTS2110C & NRTS3110C

#### Wrap-Tite, Inc.

6200 Cochran Rd.  
Solon, Ohio 44139

**Toll Free:** 888-WRAP-TITE

**Fax:** 440-349-5432  
www.wraptite.com -  
info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.