



Product Data Sheet

General Masking Tape



Product **Description**:

This general-Purpose masking tape has been designed for use as a utility grade crepe paper masking tape for non-critical applications. An excellent room temperature product which primary use includes packaging, bundling, labeling and numerous other applications where a pressure sensitive tape is needed. Designed for indoor use only and should not be subjected to outdoor exposure or prolonged sunlight as it may become difficult to remove. It is solvent and thinner resistant. Not suitable for spray painting, oven baking applications and is not recommended for exacting industrial masking.

Backing:	Saturated Semi-Crepe Paper
Adhesive:	Natural Rubber and cross- linked Resins
Color:	lvory
Elongation (% At Break)	5% (ASTM D3759)
Tensile Strength	22 lb./ in (ASTM D3759)
Adhesion to Steel	20 oz./in width (ASTM D3330)
Total Thickness:	4.3 Mil
Temperature Range:	122° F
Packaging	N/A
Country of Origin	N/A

Item ID Numbers Here:

MST5512W, MST5518W, MST5524W, MST5536W, MST5548W, MST5572W

Wrap-Tite, Inc. 6200 Cochran Rd. Solon, Ohio 44139

Toll Free: 888-WRAP-TITE

Fax: 440-349-5432 www.wraptite.com - info@wraptite.com

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.