



Product Data Sheet

Recycled PE “Bottle” Carton Sealing Tape



Product Description:

General performance, economical carton sealing tape with acrylic emulsion adhesive with performance in all temperatures. Resistant to weathering and yellowing.

Item ID Numbers

Here: RPET2110C & RPET3110C

Wrap-Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP-TITE
Fax: 440-349-5432
www.wraptite.com -
info@wraptite.com

Backing:	Post-Consumer Recycled PET 0.48 mil.
Adhesive:	Acrylic emulsion adhesive 0.72 mil.
Color(s):	Clear.
Elongation (% At Break)	100% (ASTM D3759)
Tensile Strength	15.73 lbs. / in (PSTC - 131)
Adhesion to Steel	18.3 ozf / in (PSTC - 101)
Adhesion to Fibre	20.13 ozf / in (PSTC - 101)
Total Thickness:	1.2 Mil (PSTC - 133)
Temperature Range:	14°F to 140°F (Application)
Holding Power	24H (PSTC - 107)

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.