



# Product Data Sheet

## 5" Cast Extended Core Color Stretch Film



Effective 01/2017

### Item ID Numbers:

ZEX547A-HD, ZEX563GO1, ZEX580 AL , ZEX580AR , ZEX580AW , ZEX580AY , ZEX580AG , ZEX515BB

Colors: - Emerald Green, Orange, Black, Red, White, Yellow, Green

### Nominal Values:

Film Properties	ASTM Test Method	47 Gauge	63 Gauge	80 Gauge	150 Gauge
Tensile @ Break MD (psi)	D-882	6,500	6,500	6,300	6,300
Tensile @ Break TD (psi)	D-882	4,100	4,000	4,100	4,100
Tensile @ Yield MD (psi)	D-882	1,300	1,350	1,350	1,350
Tensile @ Yield TD (psi)	D-882	1,240	1,230	1,200	1,200
Elongation MD (%)	D-882	390	420	560	540
Elongation TD (%)	D-882	610	620	620	640
Elmendorf Tear MD (g/mil)	D-1922	350	340	330	330
Elmendorf Tear TD (g/mil)	D-1922	600	550	550	550

### Core Properties

Length		10"	10"	10"	10"
Diameter		1.3"	1.3"	1.3"	1.3"
Wall Thickness		125 MIL	125 MIL	125 MIL	125 MIL

Remark:

For G, G1 Core dia. 1.78", length 3", Wall Thickness 170 mil

### Wrap Tite, Inc.

6200 Cochran Rd.  
Solon, Ohio 44139

Toll Free: 888-WRAP TITE (972-7848)

Fax: 440-349-5432

www.wraptite.com – info@wraptite.com



NOTE: MD = Machine Direction

TD = Transverse Direction