



Cast Hand Stretch Film



Product Data Sheet

Effective 01/2017

Item ID Numbers:

CHF1265A, CHF1270A, CHF1280A, CHF1290A, CHF1565A, CHF1570A, CHF1580A, CHF1590A, CHF1665A, CHF1860A, CHF1865A, CHF1870A, CHF1880A, CHF1890A, CHF18100A, CHF1812A

Nominal Values: (Tol.+/-15%)

Film Properties	ASTM Test Method	60 Gauge	65 Gauge	70 Gauge	80 Gauge	90 Gauge	100 Gauge	120 Gauge
Tensile @ Break MD (psi)	D-882	6,400	6,400	6,200	6,200	6,200	6,200	6,000
Tensile @ Break TD (psi)	D-882	4,100	4,200	4,000	4,000	4,100	4,000	4,100
Tensile @ Yield MD (psi)	D-882	1,300	1,350	1,350	1,350	1,330	1,400	1,500
Tensile @ Yield TD (psi)	D-882	1,200	1,200	1,250	1,250	1,150	1,250	1,300
Elongation MD (%)	D-882	410	420	450	520	500	525	550
Elongation TD (%)	D-882	630	640	640	660	610	600	675
Elmendorf Tear MD (g/mil)	D-1922	350	360	325	325	325	325	300
Elmendorf Tear TD (g/mil)	D-1922	600	600	560	580	590	535	530

Wrap Tite, Inc.

6200 Cochran Rd.

Solon, Ohio 44139

Toll Free: 888-WRAP TITE (972-7848)

Fax: 440-349-5432

www.wraptite.com – info@wraptite.com



NOTE: MD = Machine Direction

TD = Transverse Direction